



witloc 8mm

Description
Direct Pressure Laminate according to EN 13329 for glueless installation
Fields of use
Laminate witloc is suitable for heavy domestic and general commercial use (EN 13329 – 32)

Technical Details	
Dimensions (Décor)	1280 x 192 mm
Thickness	8 mm
Package	Carton: 9 elements / 2.21m ² / 16.25kg Pallet: 52 cartons / 114.92m ² / 865kg
Warranty	Domestic: 15 Years Commercial: 5 Years

Classification		
Level of Use 23 Heavy domestic use	EN 13329	Corridors, living rooms, kitchens, home offices
Level of use 31 Moderate commercial use	EN 13329	Offices, boutiques, cafes
Abrasion resistance	EN 13329, annex E	AC 4
Impact resistance	EN 13329, annex F	IC 2
Reaction to fire	DIN 4102 T1 EN 13501-1	B1 C _{fl} s1
Dynamic coefficient of friction	EN 13893 EN 14041	μ ≥ 0.3 DS
Resistance to staining	EN 438-2	Materials of group 1 + 2: ≥ grade 5 Materials of group 3: ≥ grade 4
Resistance to cigarette burns	EN 438-2	Slight change of the surface ≥ grade 4
Light fastness	EN ISO 105 – B02 EN 20105 – A02	Blue wool scale ≥ 6 Grey scale ≥ 4
Static indentation	EN 433	No visible change, i.e. ≤ 0.01 mm
Effect of castor chair	EN 425	No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998 5.4.4.2 (Type W) shall be used
Formaldehyde emission	DIN EN 14041	E1

Member of CELQ – Certified European Laminate Quality e. V.
Guarantees the quality of laminate flooring by determination of CELQ certified members. For more technical information contact Floating Floors Pty Ltd