



witloc 8mm

| |
|---|
| Description |
| Direct Pressure Laminate according to EN 13329 for glueless installation |
| Fields of use |
| Laminate witloc is suitable for heavy domestic and general commercial use (EN 13329 – 32) |

| | |
|---------------------------|--|
| Technical Details | |
| Dimensions (Décor) | 1280 x 192 mm |
| Thickness | 8 mm |
| Package | Carton: 9 elements / 2.21m ² / 16.25kg Pallet: 52 cartons / 114.92m ² / 865kg |
| Warranty | Domestic: 15 Years Commercial: 5 Years |

| | | |
|--|------------------------------------|---|
| Classification | | |
| Level of Use 23 Heavy domestic use | EN 13329 | Corridors, living rooms, kitchens, home offices |
| Level of use 31 Moderate commercial use | EN 13329 | Offices, boutiques, cafes |
| Abrasion resistance | EN 13329, annex E | AC 4 |
| Impact resistance | EN 13329, annex F | IC 2 |
| Reaction to fire | DIN 4102 T1 EN 13501-1 | B1 C _{fl} s1 |
| Dynamic coefficient of friction | EN 13893 EN 14041 | μ ≥ 0.3 DS |
| Resistance to staining | EN 438-2 | Materials of group 1 + 2: ≥ grade 5 Materials of group 3: ≥ grade 4 |
| Resistance to cigarette burns | EN 438-2 | Slight change of the surface ≥ grade 4 |
| Light fastness | EN ISO 105 – B02 EN 20105 – A02 | Blue wool scale ≥ 6 Grey scale ≥ 4 |
| Static indentation | EN 433 | No visible change, i.e. ≤ 0.01 mm |
| Effect of castor chair | EN 425 | No change in appearance or damage, as defined in EN 425. Single-wheel castors, as defined in EN 12529:1998 5.4.4.2 (Type W) shall be used |
| Formaldehyde emission | DIN EN 14041 | E1 |

Member of CELQ – Certified European Laminate Quality e. V.
Guarantees the quality of laminate flooring by determination of CELQ certified members. For more technical information contact Floating Floors Pty Ltd